

Aviation hose ELAFLEX HD-C 1"1/2 Length 25m - tinned brass Spannloc MM BSPP 1"1/2 fittings

Product codes:

Product attributes:

Reference:
PC270-00087
EAN13: -
UPC: -



Note: Components not true to scale. Picture may differ from original product.

Product description:

Features:

- Hose type: HD-C (delivery only)
- Nominal diameter: 38mm (1"1/2)
- Length: 25m (between sealing surfaces)
- Fittings: Spannloc male/male 1"1/2 BSPP
- Material of connections: Tinned brass

Please, for any order, select a certificate in the associated product below and add it to your cart to receive it with your hose. A certificate cannot be ordered retroactively once the hose is delivered.

Application:

The "Yellow Ring" type HD-C aviation hoses are ideal for delivering fuel to an aircraft and/or transferring fuel downstream of the pump. Please, note that you should prefer a VHD-C type if

your hose is upstream of the pump (example: defuelling application)

To comply with international norms, all aviation hoses shall have:

- an inlet /fitting
- a hose
- an outlet fitting
- a conductivity and pressure test certificate (not included, to order separately see below *associated products*)

Feel free to contact us if you are looking for a different hose configuration. Thanks to let us know:

- Both fittings diameter, type, thread, gender, and material (preferably in tinned brass for aviation refuelling application)
- the type and length of hose (between sealing surfaces)
- the type of certificate.
 - > In Europe, the certificate applicable on a aircraft refuelling site is the ADR certificate valid for 10 years.
 - > In France, the 6 years validity is required for the certificate for road transportation only as per The Transport of Dangerous Substances (TDG)