

# SONDE ELECTRONIQUE HERMETIC UTIMETER OTEX - 25M



**Product codes:**

Reference:  
PC173-00016  
EAN13: -  
UPC: -

**Product attributes:**

**Product description:**

This HERMETIC equipment is a portable multi-function gauging system designed to perform 3 measurements in one operation:

a) the hollow (U).

b) the oil/water interface (I).

tape resolution: 1 mm (1/16 ")

tape accuracy:  $\pm 1.5$  mm for 30 m ( $\pm 1/16$  " approx. for 100 feet)

accuracy of level or interface detection:  $\pm 2$  mm ( $\pm 0.08$  " approx.)

minimum level detectable at the bottom of the tank: 6 mm.

c) temperature (T) by continuous reading at any height.

ambient temperature range: -20°C to 50°C

measuring range of the probe: -40°C to 90°C

resolution: 0.01° or 0.1°, adjustable

Accuracy in the calibration range:  $\pm 0.1^\circ\text{C}$  (0°C to 70°C); Temperature scale: °C or °F, adjustable.

This HERMetic equipment meets the requirements of API MPMS Chapter 7 2001, Table 3, ISO 4268 and IP PMM Part IV. This version of the equipment is equipped with a protective cap for the probe, a protective tube under the plate and a fall arrest pin. Due to the small diameter of the probe, this device can be inserted into openings with a diameter of 30mm or more only (25mm without the probe protection cap).