

Filter cartridge FO-614A3



Product codes: Product attributes:

Reference: PC214-00241 EAN13: -UPC: -

Product description:

Specification 1440, Topequeations admigrational conferences on Academic Medication (Cuecation) (Cuecation)

- UP TO THREE TIMES GREATER SOLIDS CAPACITY than regular pleated paper cartridges
- Large Surface Area Allows high flow rate with low initial pressure drop and maximum contaminant holding capacity.
- Resin Impregnated Microglass Media Maintains strength, resists effects of water and heat.
- 75 psi Collapse Strength Heavy gauge aluminized steel center tube and injection molded end caps give safety margin against pressure surges.
- Aluminized Steel Components Resist corrosion from most industrial fluids.
- Buna-N Gaskets The best general gasket material available assures positive seal in most fluids.
- Urethane Bonding Material Endcaps urethane-bonded to media to prevent internal bypassing
- 98%+ Filtration Efficiency
- Threaded Base also available

Description:



Manufacturer: VelconPart Number: FO-614A3

• Filter Type: Microfiberglass media filter cartridge

• Micron Rating: 3

• Dimension: 6? x 14? x 3-1/2? ID

• Outer Wrap: Yes

• End Cap Style: Open End

• Maximum Flow Rate (GPM): 58

Collapse Strength: 75 psi
Operating pH Range: 5 – 9

• Maximum Operating Temperature: 250degF (121degC)

• Picture for illustration purposes only