

# Filter Cartridge OS-61286



**Product codes:**

Reference:  
PC214-00353  
EAN13: -  
UPC: -

**Product attributes:**

**Product description:**

The OS Series combination coalescer/separator cartridges filter dirt and remove water from aviation and diesel fuels. They are designed to fit into VF-61 and VF-609 housings, Facet's VFCS-21 and VFCS-22 filter/separator housings, and Racor's FBO-10 and FBO-14 housings.

• **Item Information**

Coalescer/Separator Cartridges for Aviation & Diesel Fuels

OS Series

Designed for superior performance in VF-61 & VF-609 Housings, Facet's VFCS-21 & VFCS-22 Filter/Separator Vessels & Racor's FBO-10 & FBO-14 Housings

**FEATURES**

- Can be used with pre-mixed fuel containing anti-icing additive

- One piece replacement combination coalescer and separator cartridge
- OS-51288 Cartridge: Laboratory tested to 0.2% water in incoming fuel, 10 ppm in effluent\*
- Teflon® coated screen separator
- Reliable radial sump seal design
- Nominal 0.5 micron particle efficiency for jet fuel and avgas; 5 micron for diesel fuel
- Minimum 75 psid collapse strength
- Flow direction – outside to inside
- Operating temperatures up to 240°F (115°C)
- 5 - 9 operating pH range

## Technical Specifications

- Length (inch):11 3/4
- Micron Rating (µm):5
- Brand:Velcon
- Application:Aviation, Diesel
- Media:Teflon Coated Separator with Coalescer/Filter
- Seal Material:Buna N Radial
- Outside Diameter (inch):6
- Filter Type:Coalescer Separator
- Application:Aviation, Diesel
- pH Range:Continuous Operation: 5 - 9
- Maximum Operating Temperature:240 °F, 115 °C
- Minimum Collapse Strength:75 psid